

Phonak Serenity Choice™

Reusable Earplugs

VERSION: PR-205P / 07.2020

CI 25

Music
KM 20

CI 25

Sleep
KI 25

CI 25

Shooting & Hunting
KI 12

CI 25

Comfort
KR 15

CI 25

Work
KI 25

CI 25

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|----------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.0 | 22.2 | 22.7 | 22.7 | 24.8 | 30.9 | 25.3 | 36.7 |
| SD (dB) | 3.4 | 3.0 | 2.9 | 2.6 | 2.6 | 3.3 | 2.9 | 3.5 |
| APV (dB) | 20.5 | 20.2 | 19.7 | 20.1 | 21.2 | 27.5 | 19.6 | 33.7 |

CI 25

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 22.1 | 20.7 | 20.5 | 24.3 | 31.1 | 31.6 | 21.8 | 27.7 | 32.7 |
| SD (dB) | 3.0 | 2.8 | 3.6 | 4.0 | 4.1 | 3.2 | 3.4 | 4.1 | 4.1 |
| APV (dB) | 16.1 | 15.3 | 13.1 | 16.7 | 23.1 | 19.4 | - | 20.7 | - |

CI 25

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|----------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.0 | 22.2 | 22.7 | 22.7 | 24.8 | 30.9 | 25.3 | 36.7 |
| SD (dB) | 3.4 | 3.0 | 2.9 | 2.6 | 2.6 | 3.3 | 2.9 | 3.5 |
| APV (dB) | 16.9 | 19.0 | 16.7 | 17.4 | 21.2 | 17.6 | 12.7 | 13.9 |

CI 20

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|----------|------|------|------|------|------|------|------|------|
| MA (dB) | 21.4 | 20.6 | 22.8 | 22.7 | 23.8 | 22.8 | 15.8 | 17.4 |
| SD (dB) | 4.5 | 2.6 | 5.9 | 6.3 | 4.4 | 5.2 | 2.6 | 3.6 |
| APV (dB) | 18.9 | 19.0 | 16.7 | 17.4 | 21.2 | 17.6 | 12.7 | 13.9 |

CI 20

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.8 | 21.6 | 21.8 | 25.8 | 24.7 | 15.8 | 15.6 | 17.1 | 13.3 |
| SD (dB) | 3.6 | 3.2 | 2.9 | 4.8 | 3.9 | 2.6 | 3.2 | 3.0 | 4.4 |
| APV (dB) | 18.6 | 15.2 | 15.8 | 16.7 | 15.9 | 10.0 | - | 7.9 | - |

CI 15

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 16.8 | 16.8 | 14.4 | 14.3 | 14.7 | 18.1 | 26.7 | 22.2 | 29.3 |
| SD (dB) | 3.6 | 3.4 | 2.4 | 3.2 | 3.2 | 2.9 | 2.0 | 3.7 | |
| APV (dB) | 9.5 | 10.7 | 11.9 | 11.5 | 15.8 | 22.8 | 10.2 | 16.6 | |

CI 15

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 15.2 | 15.1 | 15.6 | 19.0 | 28.1 | 24.4 | 21.5 | 17.0 | 27.2 |
| SD (dB) | 3.0 | 2.6 | 4.1 | 3.1 | 3.9 | 3.1 | 3.3 | 3.2 | 4.6 |
| APV (dB) | 8.2 | 8.9 | 8.4 | 12.8 | 20.3 | 17.2 | 17.7 | 14.5 | - |

CI 15

IPFL certification data

| Impulse peak level | 130 dB | 150 dB | 158 dB | 166 dB |
|--|--------|--------|--------|--------|
| This pulse has been acquired by testing for peak levels 130 dB and 150 dB according to ANSI S12.42-2010 and by estimation for peak levels 158 dB and 166 dB. | 26.3 | 48.3 | 31.1 | 48.3 |
| | 33.7 | 48.3 | 33.7 | 48.3 |

CI 15

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 15.2 | 15.1 | 15.6 | 19.0 | 28.1 | 24.4 | 21.5 | 17.0 | 27.2 |
| SD (dB) | 3.0 | 2.6 | 4.1 | 3.1 | 3.9 | 3.1 | 3.3 | 3.2 | 4.6 |
| APV (dB) | 8.2 | 8.9 | 8.4 | 12.8 | 20.3 | 17.2 | 17.7 | 14.5 | - |

CI 15

IPFL certification data

| Impulse peak level | 130 dB | 150 dB | 158 dB | 166 dB |
|--|--------|--------|--------|--------|
| This pulse has been acquired by testing for peak levels 130 dB and 150 dB according to ANSI S12.42-2010 and by estimation for peak levels 158 dB and 166 dB. | 26.3 | 48.3 | 31.1 | 48.3 |
| | 33.7 | 48.3 | 33.7 | 48.3 |

CI 15

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 15.2 | 15.1 | 15.6 | 19.0 | 28.1 | 24.4 | 21.5 | 17.0 | 27.2 |
| SD (dB) | 3.0 | 2.6 | 4.1 | 3.1 | 3.9 | 3.1 | 3.3 | 3.2 | 4.6 |
| APV (dB) | 8.2 | 8.9 | 8.4 | 12.8 | 20.3 | 17.2 | 17.7 | 14.5 | - |

CI 15

IPFL certification data

| Impulse peak level | 130 dB | 150 dB | 158 dB | 166 dB |
|--|--------|--------|--------|--------|
| This pulse has been acquired by testing for peak levels 130 dB and 150 dB according to ANSI S12.42-2010 and by estimation for peak levels 158 dB and 166 dB. | 26.3 | 48.3 | 31.1 | 48.3 |
| | 33.7 | 48.3 | 33.7 | 48.3 |

CI 15

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 15.2 | 15.1 | 15.6 | 19.0 | 28.1 | 24.4 | 21.5 | 17.0 | 27.2 |
| SD (dB) | 3.0 | 2.6 | 4.1 | 3.1 | 3.9 | 3.1 | 3.3 | 3.2 | 4.6 |
| APV (dB) | 8.2 | 8.9 | 8.4 | 12.8 | 20.3 | 17.2 | 17.7 | 14.5 | - |

CI 15

IPFL certification data

| Impulse peak level | 130 dB | 150 dB | 158 dB | 166 dB |
|--|--------|--------|--------|--------|
| This pulse has been acquired by testing for peak levels 130 dB and 150 dB according to ANSI S12.42-2010 and by estimation for peak levels 158 dB and 166 dB. | 26.3 | 48.3 | 31.1 | 48.3 |
| | 33.7 | 48.3 | 33.7 | 48.3 |

APPLICATIONS

CI 25

Music
KM 20

CI 25

Sleep
KI 25

CI 25

Shooting & Hunting
KI 12

CI 25

Comfort
KR 15

CI 25

Work
KI 25

CI 25

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|----------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.0 | 22.2 | 22.7 | 22.7 | 24.8 | 30.9 | 25.3 | 36.7 |
| SD (dB) | 3.4 | 3.0 | 2.9 | 2.6 | 2.6 | 3.3 | 2.9 | 3.5 |
| APV (dB) | 20.5 | 20.2 | 19.7 | 20.1 | 21.2 | 27.5 | 19.6 | 33.7 |

CI 25

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 22.1 | 20.7 | 20.5 | 24.3 | 31.1 | 31.6 | 21.8 | 27.7 | 32.7 |
| SD (dB) | 3.0 | 2.8 | 3.6 | 4.0 | 4.1 | 3.2 | 3.4 | 4.1 | 4.1 |
| APV (dB) | 16.1 | 15.3 | 13.1 | 16.7 | 23.1 | 19.4 | - | 20.7 | - |

CI 25

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|----------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.0 | 22.2 | 22.7 | 22.7 | 24.8 | 30.9 | 25.3 | 36.7 |
| SD (dB) | 3.4 | 3.0 | 2.9 | 2.6 | 2.6 | 3.3 | 2.9 | 3.5 |
| APV (dB) | 16.9 | 19.0 | 16.7 | 17.4 | 21.2 | 17.6 | 12.7 | 13.9 |

CI 20

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|----------|------|------|------|------|------|------|------|------|
| MA (dB) | 21.4 | 20.6 | 22.8 | 22.7 | 23.8 | 22.8 | 15.8 | 17.4 |
| SD (dB) | 4.5 | 2.6 | 5.9 | 6.3 | 4.4 | 5.2 | 2.6 | 3.6 |
| APV (dB) | 18.9 | 19.0 | 16.7 | 17.4 | 21.2 | 17.6 | 12.7 | 13.9 |

CI 20

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.8 | 21.6 | 21.8 | 25.8 | 24.7 | 15.8 | 15.6 | 17.1 | 13.3 |
| SD (dB) | 3.6 | 3.2 | 2.9 | 4.8 | 3.9 | 2.6 | 3.2 | 3.0 | 4.4 |
| APV (dB) | 18.6 | 15.2 | 15.8 | 16.7 | 15.9 | 10.0 | - | 7.9 | - |

CI 15

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 | |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 16.8 | 16.8 | 14.4 | 14.3 | 14.7 | 18.1 | 26.7 | 22.2 | 29.3 |
| SD (dB) | 3.6 | 3.4 | 2.4 | 3.2 | 3.2 | 2.9 | 2.0 | 3.7 | |
| APV (dB) | 9.5 | 10.7 | 11.9 | 11.5 | 15.8 | 22.8 | 10.2 | 16.6 | |

CI 15

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 15.2 | 15.1 | 15.6 | 19.0 | 28.1 | 24.4 | 21.5 | 17.0 | 27.2 |
| SD (dB) | 3.0 | 2.6 | 4.1 | 3.1 | 3.9 | 3.1 | 3.3 | 3.2 | 4.6 |
| APV (dB) | 8.2 | 8.9 | 8.4 | 12.8 | 20.3 | 17.2 | 17.7 | 14.5 | - |

CI 15

IPFL certification data

| Impulse peak level | 130 dB | 150 dB | 158 dB | 166 dB |
|--|--------|--------|--------|--------|
| This pulse has been acquired by testing for peak levels 130 dB and 150 dB according to ANSI S12.42-2010 and by estimation for peak levels 158 dB and 166 dB. | 26.3 | 48.3 | 31.1 | 48.3 |
| | 33.7 | 48.3 | 33.7 | 48.3 |

CI 15

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 15.2 | 15.1 | 15.6 | 19.0 | 28.1 | 24.4 | 21.5 | 17.0 | 27.2 |
| SD (dB) | 3.0 | 2.6 | 4.1 | 3.1 | 3.9 | 3.1 | 3.3 | 3.2 | 4.6 |
| APV (dB) | 8.2 | 8.9 | 8.4 | 12.8 | 20.3 | 17.2 | 17.7 | 14.5 | - |

CI 15

IPFL certification data

| Impulse peak level | 130 dB | 150 dB | 158 dB | 166 dB |
|--|--------|--------|--------|--------|
| This pulse has been acquired by testing for peak levels 130 dB and 150 dB according to ANSI S12.42-2010 and by estimation for peak levels 158 dB and 166 dB. | 26.3 | 48.3 | 31.1 | 48.3 |
| | 33.7 | 48.3 | 33.7 | 48.3 |

CI 15

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 15.2 | 15.1 | 15.6 | 19.0 | 28.1 | 24.4 | 21.5 | 17.0 | 27.2 |
| SD (dB) | 3.0 | 2.6 | 4.1 | 3.1 | 3.9 | 3.1 | 3.3 | 3.2 | 4.6 |
| APV (dB) | 8.2 | 8.9 | 8.4 | 12.8 | 20.3 | 17.2 | 17.7 | 14.5 | - |

CI 15

IPFL certification data

| Impulse peak level | 130 dB | 150 dB | 158 dB | 166 dB |
|--|--------|--------|--------|--------|
| This pulse has been acquired by testing for peak levels 130 dB and 150 dB according to ANSI S12.42-2010 and by estimation for peak levels 158 dB and 166 dB. | 26.3 | 48.3 | 31.1 | 48.3 |
| | 33.7 | 48.3 | 33.7 | 48.3 |

KIM 12

PHONAK SERENITY CHOICE™ REUSABLE EARPLUGS

CI 25

Music
KM 20

CI 25

Sleep
KI 25

CI 25

Shooting & Hunting
KI 12

CI 25

Comfort
KR 15

CI 25

Work
KI 25

CI 25

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|----------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.0 | 22.2 | 22.7 | 22.7 | 24.8 | 30.9 | 25.3 | 36.7 |
| SD (dB) | 3.4 | 3.0 | 2.9 | 2.6 | 2.6 | 3.3 | 2.9 | 3.5 |
| APV (dB) | 20.5 | 20.2 | 19.7 | 20.1 | 21.2 | 27.5 | 19.6 | 33.7 |

CI 25

ANSI certification data

| F (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |
|----------|------|------|------|------|------|------|------|------|------|
| MA (dB) | 22.1 | 20.7 | 20.5 | 24.3 | 31.1 | 31.6 | 21.8 | 27.7 | 32.7 |
| SD (dB) | 3.0 | 2.8 | 3.6 | 4.0 | 4.1 | 3.2 | 3.4 | 4.1 | 4.1 |
| APV (dB) | 16.1 | 15.3 | 13.1 | 16.7 | 23.1 | 19.4 | - | 20.7 | - |

CI 25

CE certification data

| F (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|---------|------|------|------|------|------|------|------|------|
| MA (dB) | 23.0 | 22.2 | 22.7 | 22.7 | 24.8 | 30.9 | | |

